

PIXELPRO

SPECIFICATION SHEET

AIR Series (Indoor)



Model Name	AIR-1i	AIR-2i	AIR-3i	AIR-4i
Pixel Pitch	1.9mm	2.9mm	3.9mm	4.8mm
Pixel Density	262,144	112,896	65,536	43264
LED Type	SMD1515	SMD2121	SMD2121	SMD2121
Module Size	250*250	250*250	250*250	250*250
Viewing Angle	H160/V120	H160/V120	H160/V120	H160/V120
Brightness (nits)	800	800	800	800
Grey Scale	14 Bit	14 Bit	14 Bit	14 Bit
Refresh Rate (Hz)	1920	1920	1920	1920
Maximum Power Draw	400w	400w	400w	400w
Average Power Draw	120w	120w	120w	120w
Cabinet Size (mm)	500*500	500*500	500*500	500*500
Cabinet Weight	14.1 lbs	14.1 lbs	14.1 lbs	14.1 lbs
Cabinet Resolution (Pixels)	256x256	168x168	128x128	104x104
Input Voltage	AC 110-240V	AC 110-240V	AC 110-240V	AC 110-240V
Working Temperature	-5°F ~ 122°F	-5°F ~ 122°F	-5°F ~ 122°F	-5°F ~ 122°F
Working Humidity(RH)	10%-90%	10%-90%	10%-90%	10%-90%
Ingress Protection	IP20	IP20	IP20	IP20
Estimated Life Span	50,000+ Hours	50,000+ Hours	50,000+ Hours	50,000+ Hours
Maintenance	Rear	Rear	Rear	Rear
Rigging Options	Fly/Stack	Fly/Stack	Fly/Stack	Fly/Stack

www.PixelProLED.com

Specifications are subject to change without notice